

### Flex Strip Series

# HFLX-HB60W



**LM79 LM80**

### Specifications

Type	High brightness LED flex strip
Beam Angle	115°
Input Voltage	12vDC
Power	1 m: 12 w / 5 m: 48 w
Length	5 m
Protection Grade	IP33
Packaging	Anti-static bag
Warranty	5 Year (Product)
Operating Temp.	-25 ~ +60 °C / -13 ~ +140 °F
Storage Temp.	-25 ~ +70 °C / -13 ~ +158 °F

Color	Part#	Color Temp	Lumens
Pure White	HFLX-HB60WPURE	6000k	980 lm/m

### Features

- High brightness for extreme bright needs
- Offers a variety of brightness, LED spacing and color temperatures
- Easy installation: wires pre-soldered & double-sided 3M™ tape for application
- For indoor signs, shallow cabinets or push through letters
- For lighting enhancement or decorative lighting applications
- Easy connect wires available ([download info here](#))

MODEL	MAX POWER SUPPLY LOAD			
	35W	60W	100W	150W
All models	2 meters	5 meters	8 meters	12 meters

**HanleyLED recommends underloading any power supply by 15%**

### Profile Drawings

Unit: mm [in]

Max-Cascading Quantity: 5 meters

