

Flex Strip Series

HFLX-SB60



LM79 LM80

Features

- Can be cut at pre-marked soldering points
- Standard brightness
- Offers a variety of brightness, LED spacing and color temperatures
- Easy installation: wires pre-soldered & double-sided 3M™ tape for application
- For indoor signage, lighting enhancement, or decorative illumination
- Easy connect wires available ([download info here](#))

Specifications

Type	LED flex strip
Beam Angle	115°
Input Voltage	12vDC
Power	1m: 6w / 5m: 25w
Length	5 m
Protection Grade	IP33
Packaging	Anti-static bag
Warranty	5 Year (Product)
Operating Temp.	-25 ~ +60 °C / -13 ~ +140 °F
Storage Temp.	-25 ~ +70 °C / -13 ~ +158 °F

Color	Part#	Color Temp	Lumens
Pure White	HFLX-SB60WPURE	7000K	420 lm/m
Day White	HFLX-SB60WDAY	4500K	420 lm/m
Warm White	HFLX-SB60WWARM	2800K	420 lm/m
Blue	HFLX-SB60WBLUE	470K	78 lm/m
Red	HFLX-SB60WRED	620K	76 lm/m

MODEL	MAX POWER SUPPLY LOAD			
	35W	60W	100W	150W
All models	5 meters	10 meters	16 meters	25 meters

HanleyLED recommends underloading any power supply by 15%

Profile Drawings

Max-Cascading Quantity: 5 meters

Unit: mm [in]

