

HanleyLED

HanleyLED Side By Side Comparison

CHANNEL LETTER SOLUTIONS

12vDC Input Voltage


LM79 **LM80**
L70:5+ YEARS

Part#	Color	Viewing Angle	Lumen Output	Watts/Module	Modules/Foot (fully stretched)	Max Spacing	Color Temp	Ideal Depth	Packaging	Warranty
HLED-K2030W HLED-K2030WWARM HLED-K2030R <i>(Kestrel Series - Mini)</i>	Pure White Warm White Red	120°	24 lm/mod (120 lm/ft.) 24 lm/mod (120 lm/ft.) 6 lm/mod (30 lm/ft.)	0.33	5	4"	7000K 3000 ~ 3300K 620 ~ 625K	1.5 - 8"	Anti-static bag, 300 mods (60ft)	5 year product 5 year labor
HLED-K2048 <i>(Kestrel Series)</i>	Pure White	120°	40 lm/mod (120 lm/ft.)	0.48	3	6"	7000K	4 - 8"	Anti-static bag, 100 mods (33.3ft)	5 year product 5 year labor
HLED-KD3072WCOO HLED-KD3072WPUR HLED-KD3072R <i>(Kestrel Series - Dome)</i>	Cool White Pure White Red	Wide 160°	70 lm/mod (122.5 lm/ft.) 70 lm/mod (122.5 lm/ft.) 19 lm/mod (33.25 lm/ft.)	0.72	1.75	8"	7000K 9500 ~ 11000K 620 ~ 625K	3-8"	Anti-static bag, 100 mods (57ft)	5 year product 5 year labor
HLED-P2072WCOOL HLED-P2072W HLED-P2072WWARM HLED-P2072B HLED-P2072G HLED-P2072Y HLED-P2072R <i>(Peregrine Series)</i>	Cool White Pure White Warm White Blue Green Yellow Red	Wide 160°	70 lm/mod (140 lm/ft.) 70 lm/mod (140 lm/ft.) 70 lm/mod (140 lm/ft.) 7 lm/mod (14 lm/ft.) 37 lm/mod (74 lm/ft.) 13 lm/mod (26 lm/ft.) 13 lm/mod (26 lm/ft.)	0.72	2	8"	9500 ~ 11000K 7000K 3000 ~ 3300K 465 ~ 470K 525 ~ 530K 585 ~ 590K 620 ~ 625K	2.5-8"	Anti-static bag, 100 mods (50ft)	5 year product 5 year labor
HLED-P3072W HLED-P3072R HLED-P3072W5K <i>(Peregrine Series)</i>	Pure White Red White 5K	Wide 160°	75 lm/mod (118 lm/ft.) 18 lm/mod (28 lm/ft.) 75 lm/mod (118 lm/ft.)	0.72	1.57	10"	7000K 620 ~ 625K 5000K	2.5-8"	Anti-static bag, 100 mods (63.7ft)	5 year product 5 year labor
HFLX-SB60WPURE HFLX-SB60WDAY HFLX-SB60WWARM HFLX-SB60WBLUE HFLX-SB60WRED <i>(Hanley Flex Series)</i>	Pure White Day White Warm White Blue Red	115°	420 lm/meter 420 lm/meter 420 lm/meter 78 lm/meter 76 lm/meter	6 w/meter	60 mods/meter	-	7000K 4500K 2800K 470K 620K	-	5 meter reels	5 year product
HFLX-HB60WPURE <i>(Hanley Flex Series)</i>	Pure White	115°	980 lm/meter	12 w/meter	60 mods/meter	-	7000K	-	5 meter reels	5 year product
HLED-PH203072W	Pure White	Wide 160°	80 lm/mod (128 lm/ft.)	0.72	1.6	10"	7000K	3-8"	Anti-static bag, 80 mods (50ft)	7 year product 5 year labor
HLED-PH203140W	Pure White	Wide 160°	140 lm/mod (224 lm/ft.)	1.4	1.6	12"	7000K	6-12"	Anti-static bag, 50 mods (31.25ft)	7 year product 5 year labor
HLED-RGB2072	Red Green Blue	160°	4 lm/mod 8.5 lm/mod 3 lm/mod	0.72	1.53	8"	620 ~ 625K 520 ~ 525K 470 ~ 475K	3-8"	Anti-static bag, 75 mods (50ft)	5 year product 5 year labor

HanleyLED Side By Side Comparison

CABINET SOLUTIONS



Part#	Color	Viewing Angle	Lumen Output	Watts/Module	Modules/Foot (fully stretched)	Max Spacing	Color Temp	Ideal Depth	Packaging	Warranty	Input Voltage
HLED-P3120W HLED-P3120R <i>(Peregrine Series)</i>	Pure White Red	Wide 160°	116 lm/mod (182 lm/ft.) 43 lm/mod (68 lm/ft.)	1.2	1.57	12"	7000K 620 ~ 625K	6-12"	Anti-static bag, 100 mods (63.7ft)	5 year product 5 year labor	12v
HLED-P4144 HLED-P4144R <i>(Peregrine Series)</i>	Pure White Red	Wide 160°	140 lm/mod (225.4 lm/ft.) 52 lm/mod (83.72 lm/ft.)	1.44	1.61	15"	7000K 620 ~ 625K	7-15"	Anti-static bag, 50 mods (31ft)	5 year product 5 year labor	12v
HLED-G1270 <i>(Golden Series)</i>	Pure White	10° x 40° directional beam	277 lm/mod (554 lm/ft.)	2.7	1.3	9" between mods	7000K	5- 48"	Boxed in foam tray, 60 mods (46ft)	5 year product 5 year labor	12v
HLED-WS1120W <i>(Wingspan Series)</i>	Pure White	170° wing span	115 lm/mod (264 lm/ft.)	1.2	2.3	12"	7000K	1.5-8"	Anti-static bag, 80 mods (35ft)	5 year product 5 year labor	12v
HLED-WS1240 <i>(Wingspan Series)</i>	Pure White	170° wing span	215 lm/mod (279.5 lm/ft.)	2.4	1.3	24"	7000K	6-18"	Anti-static bag, 66 mods (51ft)	5 year product 5 year labor	12v
HLED-WS3360W24 HLED-WS3360W24S	Pure White White	170° wing span	310 lm/mod (264 lm/ft)	3.6	0.85	30"	6500K 5000K	6-24"	Anti-static bag, 25 mods (29.5ft)	5 year product 5 year labor	24v

HanleyLED Light Bars

Part#	Color	Viewing Angle	Lumen Output	Watts	Color Temp	Ideal Depth	Packaging	Warranty	Input Voltage
HLED-TS510505K HLED-TS5105065K HLED-TS306505K HLED-TS306565K <i>(Tradeshow Series)</i>	Neutral White Pure White Neutral White Pure White	10° x 40° beam	1200 700	10.5 6.5	5000K 6500K 5000K 65000K	Single sided cabinet 3-12", Double sided cabinet 1.5-12"	10 pc/box	5 year product	24v
HLB-2S18 15" HLB-2S24 21" HLB-2S30 27" HLB-2S36 33.1" HLB-2S42 39.1" HLB-2S48 45" HLB-2S60 57" HLB-2S64 61.1" HLB-2S72 69" HLB-2S84 81" HLB-2S96 93" HLB-2S108 105" HLB-2S117 114" HLB-2S120 117" <i>(Concorde Cabinet System)</i>	Pure White	Wide 160°	750 800 1300 1350 1800 1900 2300 2650 2850 3250 3800 4150 4650 4750	6.3 8.2 11.6 13.5 15.2 18.8 24 24.5 29.5 34.5 40 45 44 50.5	7000K	6-30"	All components needed to assemble your fluorescent replacement length are included in the box. Pick the size you want and you'll receive everthing you need to assemble the light bar.	5 year product 5 year labor	24v



HanleyLED Side By Side Comparison

POWER SUPPLIES



Part#	Variable Input Voltage	Output Voltage	Power Recommendation	IP Rating	Features	Warranty
H60W-PPS5	100 - 277v	12v	100% power load tested. HanleyLED recommends underloading 15% whenever possible.	IP68	· Premium quality · Waterproof! · Aluminum case for optimal heat distribution · Suited for wet, damp, & dry locations	5 year*
H60W-PPS277	100 - 277v	12v	100% power load tested. HanleyLED recommends underloading 15% whenever possible.	IP68	· Premium quality · Waterproof! · Aluminum case for optimal heat distribution · Suited for wet, damp, & dry locations	3 year*
H100W-PPS5	100 - 277v	12v	100% power load tested. HanleyLED recommends underloading 15% whenever possible.	IP68	· Premium quality · Waterproof! · Aluminum case for optimal heat distribution · Suited for wet, damp, & dry locations	5 year*
H100W-PPS277	100 - 277v	12v	100% power load tested. HanleyLED recommends underloading 15% whenever possible.	IP68	· Premium quality · Waterproof! · Aluminum case for optimal heat distribution · Suited for wet, damp, & dry locations	3 year*
H150W-PPS5	100-277v	12v	100% power load tested. HanleyLED recommends underloading 15% whenever possible.	IP68	· Premium quality · Waterproof! · Aluminum case for optimal heat distribution · Suited for wet, damp, & dry locations	5 year*
H60W-PPS524V	100 - 277v	24v	100% power load tested. HanleyLED recommends underloading 15% whenever possible.	IP68	· Premium quality · Waterproof! · Aluminum case for optimal heat distribution · Suited for wet, damp, & dry locations	5 year*
H100W-PPS524V	100 - 277v	24v	100% power load tested. HanleyLED recommends underloading 15% whenever possible.	IP68	· Premium quality · Waterproof! · Aluminum case for optimal heat distribution · Suited for wet, damp, & dry locations	5 year*
H150W-PPS524V	100 - 277v	24v	100% power load tested. HanleyLED recommends underloading 15% whenever possible.	IP68	· Premium quality · Waterproof! · Aluminum case for optimal heat distribution · Suited for wet, damp, & dry locations	5 year*
H90W-ADP24V	90 - 264v	12v	89%	-	Power source for the HanleyLED Tradeshow modules (HLED-TS510505K and HLED-TS5105065K). Indoor use only.	3 year*
H60W-PPS7SLM	100 - 277v	12v	100% power load tested. HanleyLED recommends underloading 15% whenever possible.	IP68	· Ultra Slim! · Premium quality · Waterproof! · Aluminum case for optimal heat distribution · Suited for wet, damp, & dry locations	7 year*
H60W-PPSE	100 - 277v	12v	85%	IP67	· Premium quality · Waterproof! · Budget friendly 100v-277v LED driver solution · Suited for wet, damp, & dry locations	3 year**

*2 year labor warranty if paired with HanleyLED modules, 1 year labor warranty if paired with any other qualified LEDs.

**1 year labor warranty; no labor warranty if not paired with HanleyLED modules.