

### Flex Strip Series

# HFLX-SB60



**LM79 LM80**

### Features

- Can be cut at pre-marked soldering points
- Standard brightness
- Offers a variety of brightness, LED spacing and color temperatures
- Easy installation: wires pre-soldered & double-sided 3M™ tape for application
- For indoor signage, lighting enhancement, or decorative illumination
- Easy connect wires available ([download info here](#))

### Specifications

<b>Type</b>	LED flex strip
<b>Beam Angle</b>	115°
<b>Input Voltage</b>	12vDC
<b>Power</b>	1m: 6w / 5m: 25w
<b>Length</b>	5 m
<b>Protection Grade</b>	IP33
<b>Packaging</b>	Anti-static bag
<b>Warranty</b>	5 Year (Product)
<b>Operating Temp.</b>	-25 ~ +60 °C / -13 ~ +140 °F
<b>Storage Temp.</b>	-25 ~ +70 °C / -13 ~ +158 °F

Color	Part#	Color Temp	Lumens
Pure White	HFLX-SB60WPURE	6500K	420 lm/m
Day White	HFLX-SB60WDAY	5000K	420 lm/m
Warm White	HFLX-SB60WWARM	2800K	420 lm/m
Blue	HFLX-SB60WBLUE	470K	78 lm/m
Red	HFLX-SB60WRED	620K	76 lm/m

MODEL	MAX POWER SUPPLY LOAD			
	35W	60W	100W	150W
All models	5 meters	10 meters	16 meters	25 meters

### Profile Drawings

Max-Cascading Quantity: 5 meters

Unit: mm [in]

